

TGC® Black Nitrile Disposable Gloves

Intended Use

To protect the user from incidental harmful chemical and substance contamination within industry and trade based work environments.

Trade Name TGC Black Nitrile	Materials Nitrile (Carboxylated	Cuff Finishing Beaded	Type Single-use only, ambidextrous, low-
Gloves	Butadiene Acrylonitrile)		sweat, powder free.
Colour	Surface Finish	Product Conformance	
Black	Full Textured	ASTM D6319 Current Revision and Customer Requirement.	

Glove Standard





Type B JKOPT

Part No.	
Extra Small	160000
Small	160001
Medium	160002
Large	160003
Extra Large	160004

Dimensions	Size	Palm width	Length (mm)
Millimetres (Inches)	Extra Small	85 ± 5mm (3.35" ± 0.2")	240 (minimum) (9")
	Small	95 ± 5mm (3.74" ± 0.2")	240 (minimum) (9")
	Medium	106 ± 5mm (4.17" ± 0.2")	240 (minimum) (9")
	Large	115 ± 5mm (4.53" ± 0.2")	240 (minimum) (9")
	Extra Large	120 ± 5mm (4.72" ± 0.2")	240 (minimum) (9")

Thickness	Cuff	Palm	Finger	Beading
Millimetres Single wall thickness mm (Inches)		0.12 - 0.15mm (4.7mils - 5.9mils)		0.5min

Packaging Configuration & Labelling

GS1 format

Packaging Con	ilguration & Labelling
Packaging	100 gloves per inner box (by weight) 10 Boxes per Outer Carton
Box dimension	240mm(L) x 125mm(W) x 75mm(D)
Labelling	The inner boxes and outer cartons have the following information: Product description, brand, size, and net quantity of gloves. Country of origin, name and address of distributor, and single use only symbol.

Physical Properties	Un-Aged Spec	Aged Spec
Tensile Strength (MPa)	14 min	14 min
Ultimate Elongation (%)	500 min	400 min





Barcodes